

SOLYX®

SX-1002 Clear Sand Blast



Product Details

SX-1002 Clear Sand Blast is a durable, embossed vinyl film made to replicate the look of sandblasted glass. Supplied with a silicone coated liner and pressure-sensitive adhesive, it is recommended for application to interior glass and exterior glass and is ideal for privacy, decorative, or architectural applications.

Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

| Product Code | SX-1002 |
|----------------------------|----------------------|
| Film Type | Polymeric Vinyl |
| Adhesive Type | Pressure-sensitive |
| Usage | Interior or Exterior |
| Available Roll Width(s) | 36", 48", 60" |
| Thickness | 150 micron |
| Shading Coefficient | 0.93% |
| Visible Light Reflection | 70% |
| Visible Light Transmission | 53% |
| Infra-Red Transmission | 50% |
| UV Transmission | 22% |
| Solar Heat Reflection | 7% |
| Solar Heat Transmission | 76% |

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. Exterior applications have a three (3) year warranty. See warranty information for specific details.

To ensure that **Genuine Solyx**® products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit www.glassfilms.eu/validate to validate.



Product Construction

Face Film

127 micron PVC

Adhesive

Clear, Pressure-sensitive, 17 - 22 micron

Release Liner

Silicone Coated

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366 Email: sales@glassfilms.eu Web: www.glassfilms.eu