


SOLYX®

SX-5035 Subsonic



Product Details

SX-5035 Subsonic. Thin, broken, wavy lines of frost and white. Lines stretch down the length of the roll. Ideal for obscuring direct visibility and allows excellent light transmission.

Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SX-5035
Film Type	PVC
Adhesive Type	Pressure-Sensitive
Usage	Interior
Available Roll Width(s)	48"
Thickness	100 micron
Visible Light Transmission	25%
UV Transmission	23%
Infra-Red Transmission	38%
Total Solar Energy Rejected	38%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit www.glassfilms.eu/validate to validate.



Product Construction

Face Film

100 micron PVC

Adhesive

Clear, Pressure-sensitive

Release Liner

Silicone Coated

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: sales@glassfilms.eu

Web: www.glassfilms.eu