

## SOLYX®

## SX-9000 Clear Waters



### Product Details

Clear Waters Translucent clear (colourless) embossed vinyl film. Pattern runs down the length of the roll. Vertically installed. Has the appearance of ocean waves when installed horizontally. Ideal for semi-obscurating direct visibility while allowing good light transmission.

### Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

### Specification

Product Code	SX-9000
Film Type	Vinyl
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	48", 60"
Thickness	100 micron
Shading Coefficient	.93%
Visible Light Transmission	58%
Visible Light Reflection	8%
UV Transmission	48%
Solar Heat Reflection	7%
Solar Heat Transmission	76%
Infra-Red Transmission	55%

### Installation & Warranty

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit [www.glassfilms.eu/validate](http://www.glassfilms.eu/validate) to validate.



### Product Construction

#### Face Film

100 micron Vinyl

#### Adhesive

Clear, Pressure-sensitive – 0.7 – 0.87 mil

#### Release Liner

Silicone Coated

### Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

#### Contact Information

Glass Films

Tel: +44 (0) 800 970 6366  
Email: [sales@glassfilms.eu](mailto:sales@glassfilms.eu)  
Web: [www.glassfilms.eu](http://www.glassfilms.eu)