

# SOLYX®

# SX-C387 Linen



## **Product Details**

SX-C387 Linen Window Film. 60" wide Thin Wavy white line linen pattern. A subtle design providing semi-obscurity.

## Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.** 

When applied to glass or plastic surfaces: Horizontal Burn (Flame Spread) ASTM D-635 inch Less than 1.0 UL 94 Rating UL Classification V-O Class A 0 -25 Flame Spread Index 0 -450

## **Specification**

Product Code	SX-C387
Film Type	Polyester
Adhesive Type	Pressure-Sensitive
Usage	Interior
Available Roll Width(s)	60"
Thickness	51 micron
Shading Coefficient	.93%
Visible Light Reflection	70%
Visible Light Transmission	30%
UV Transmission	24%
Solar Heat Reflection	7%
Solar Heat Transmission	76%
Infra-Red Transmission	39%

## **Installation & Warranty**

#### **Installation**

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

To ensure that **Genuine Solyx**® products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit <a href="https://www.glassfilms.eu/validate">www.glassfilms.eu/validate</a> to validate.



# **Product Construction**

#### Face Film

51 micron Polyester

## Adhesive

Clear, Pressure-sensitive – 0.7 – 0.87 mil

### **Release Liner** 38 micron Silicone

# **Distribution & Contact Information**

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

#### **Contact Information**

Glass Films

Tel: +44 (0) 800 970 6366 Email: sales@glassfilms.eu Web: www.glassfilms.eu