

SOLYX®

SXHP-2411 White Stripes



Product Details

SXHP-2411 White Stripes 11/16" separated by 1/4" clear lines. Ideal for obscuring semi-direct visibility and allows excellent light transmission.

Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

Horizontal Burn (Flame Spread) ASTM D-635 inch
Less than 1.0
UL 94 Rating UL 94 Classification V-O
Class A 0 -25 Flame Spread Index 0 -450 Smoke
Developed Index

Specification

Product Code	SXHP-2411
Film Type	PET
Adhesive Type	Pressure-Sensitive
Usage	Interior
Available Roll Width(s)	48"
Thickness	38 micron
Visible Light Transmission	65%
UV Transmission	57%
Infra-Red Transmission	74%
Total Solar Energy Rejected	32%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit www.glassfilms.eu/validate to validate.



Product Construction

Face Film

38 micron PET

Adhesive

Clear, Pressure-sensitive

Release Liner

Silicone

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: sales@glassfilms.eu

Web: www.glassfilms.eu