

## SOLYX®

## SXJ-0592 Isoline Dual Frost Gradient



### Product Details

SXJ-0592 Isoline Dual Frost Gradient (revised colour). A horizontal, lineal, dual-fading gradient with a grey frosted lines design. Lines become narrower from the centre band up and down. Excellent for semi-privacy while still allowing excellent light transmission.

### Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

### Specification

Product Code	SXJ-0592
Film Type	Polyester
Adhesive Type	Removable PS
Usage	Interior
Available Roll Width(s)	60"
Thickness	100 micron
Shading Coefficient	0.55%
Visible Light Reflection	27%
Visible Light Transmission	23%
UV Transmission	2%
IR Transmission	70%
Total Solar energy Rejected	38%
Solar Energy Absorbed	25%

### Installation & Warranty

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit [www.glassfilms.eu/validate](http://www.glassfilms.eu/validate) to validate.



### Product Construction

#### Face Film

100 micron Polyester

#### Adhesive

Clear, Removable, Pressure-Sensitive

#### Release Liner

Silicone Coated

### Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

#### Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: [sales@glassfilms.eu](mailto:sales@glassfilms.eu)

Web: [www.glassfilms.eu](http://www.glassfilms.eu)