

## SOLYX®

## SXJ-0598 Dual Misty Frost Gradient



### Product Details

SXJ-0598 Dual Misty Frost Gradient (revised colour). A misty, grey, frosted, dual-fading gradient. Fades from the centre, most private area, up and down to clear. Excellent for semi-privacy while still allowing excellent light transmission. This film is installed as a horizontal band, 60" high. A solid match for this film is the SXJ-0597 Isoline Frost.

### Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

### Specification

|                                    |                      |
|------------------------------------|----------------------|
| <b>Product Code</b>                | SXJ-0598             |
| <b>Film Type</b>                   | Polyester            |
| <b>Adhesive Type</b>               | Removable PS         |
| <b>Usage</b>                       | Interior or Exterior |
| <b>Available Roll Width(s)</b>     | 60"                  |
| <b>Thickness</b>                   | 100 micron           |
| <b>Shading Coefficient</b>         | 0.55%                |
| <b>Visible Light Reflection</b>    | 27%                  |
| <b>Visible Light Transmission</b>  | 69%                  |
| <b>UV Transmission</b>             | 2%                   |
| <b>IR Transmission</b>             | 70%                  |
| <b>Total Solar energy Rejected</b> | 38%                  |
| <b>Solar Energy Absorbed</b>       | 25%                  |

### Installation & Warranty

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit [www.glassfilms.eu/validate](http://www.glassfilms.eu/validate) to validate.



### Product Construction

#### Face Film

100 micron Polyester

#### Adhesive

Clear, Removable, Pressure-Sensitive

#### Release Liner

Silicone Coated

### Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

#### Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: [sales@glassfilms.eu](mailto:sales@glassfilms.eu)

Web: [www.glassfilms.eu](http://www.glassfilms.eu)