


# SOLYX®





# **Product Details**

SXWF-SSO Satin Silver Opaque. Satin Silver opaque polyester. Easy to install. Matches Natural Anodized Aluminium. 95% Light block. Zero visibility. The front surface of this film has a light white/silver matt satin finish. The adhesive side has a metalized silver finish.

### Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.** 

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

# **Specification**

Product Code	SXWF-SSO
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior or Exterior
Available Roll Width(s)	60"
Thickness	102 micron
Visible Light Transmission	0%
UV Transmission	0%
Total Solar Absorbance	35%
Total Solar Reflectance	48%
Glare Reduction	92%
Total Solar Energy Rejected	66%
Shading Coefficient	0.24

# **Installation & Warranty**

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

## Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. Exterior applications have a three (3) year warranty. See warranty information for specific details.

To ensure that **Genuine Solyx**® products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit www.qlassfilms.eu/validate to validate.



# **Product Construction**

#### Face Film

102 micron Polyester

# **Adhesive**

Clear, Pressure-sensitive

## Release Liner

Silicone Coated

# **Distribution & Contact Information**

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

### **Contact Information**

Glass Films

Tel: +44 (0) 800 970 6366 Email: sales@glassfilms.eu Web: www.glassfilms.eu